




|                                   |                                     |                              |                     |
|-----------------------------------|-------------------------------------|------------------------------|---------------------|
| O.D. (D):                         | 1.000 in (25.4 mm)                  | Static Torque:               | 6.8 Nm              |
| Brand:                            | Ruland                              | Number of Screws:            | 2 ea                |
| Seating Torque:                   | 2.1 Nm                              | Bore Tolerance:              | +0.03 mm / -0.00 mm |
| Product Group:                    | Bellows Coupling<br>Standard Length | Material:                    | Aluminum            |
| Shaft Tolerance:                  | +0.000 mm / -0.013 mm               | Bore (B1):                   | 7 mm                |
| Zero-Backlash?:                   | Yes                                 | Bore (B2):                   | 6 mm                |
| Balanced Design:                  | Yes                                 | Keyway:                      | Yes                 |
| UNSPC:                            | 31163018                            | Keyway (K1):                 | 2 mm                |
| Cap Screw:                        | M3                                  | Keyway (K2):                 | NK                  |
| Hex Wrench Size:                  | 2.5 mm                              | B2 Max Shaft<br>Penetration: | 15.9 mm             |
| Dynamic Torque<br>Reversing:      | 1.70 Nm                             | B1 Max Shaft<br>Penetration: | 15.9 mm             |
| Dynamic Torque Non-<br>Reversing: | 3.40 Nm                             | Length (L):                  | 1.345 in (34.2 mm)  |
| Torsional Stiffness:              | 27 Nm/Deg                           | Screw Material:              | Alloy Steel         |
| Angular Misalignment:             | 1.5 deg                             | Screw Finish:                | Black Oxide         |
| Parallel Misalignment:            | 0.10 mm                             | ISO 9001:2015:               | Certified           |
| Axial Motion:                     | 0.30 mm                             | REACH:                       | Compliant           |
| Bellows Attachment<br>Method:     | Epoxy                               | RoHS3:                       | Compliant           |
| Length Tolerance:                 | +/- 0.76 mm                         | Conflict Minerals:           | Compliant           |
| Maximum Speed:                    | 10000 RPM                           | Tariff Code:                 | 8483.60.8000        |
| Temperature:                      | -40°F to 200°F (-40°C to<br>93°C)   | Recommended Hex<br>Key:      | Metric Hex Keys     |

COMPONENT

Bellows Coupling Standard  
Length



Pacific International Bearing, Inc.  
33258 Central Ave, Union City, CA 94587  
1-800-228-8895, 510-512-7000,  
info@pibsales.com  
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

**MBCK25-7-6-A**  
**Ruland**  
7mm X 6mm Bores, 25.4mm Od, 34.2mm  
Length, Bellows Coupling With Keyways,  
High Stiffness, Aluminum

|        |
|--------|
| UNIT   |
| Metric |
| SHEET  |