




|                               |                                  |                           |                     |
|-------------------------------|----------------------------------|---------------------------|---------------------|
| O.D. (D):                     | 3.125 in (79.4 mm)               | Torsional Stiffness:      | 395.5 Nm/Deg        |
| Brand:                        | Ruland                           | Screw Material:           | Alloy Steel         |
| Angular Misalignment:         | 2.0 deg                          | B2 Max Shaft Penetration: | 44.5 mm             |
| Zero-Backlash?:               | Yes                              | Bore (B1):                | 35 mm               |
| Balanced Design:              | Yes                              | Bore (B2):                | 30 mm               |
| UNSPC:                        | 31163018                         | Keyway:                   | Yes                 |
| Cap Screw:                    | M8                               | Keyway (K1):              | 10 mm               |
| Static Torque:                | 152 Nm                           | Keyway (K2):              | 8 mm                |
| Dynamic Torque Reversing:     | 38 Nm                            | B1 Max Shaft Penetration: | 44.5 mm             |
| Hex Wrench Size:              | 6.0 mm                           | Seating Torque:           | 39 Nm               |
| Dynamic Torque Non-Reversing: | 76 Nm                            | Length (L):               | 3.808 in (96.7 mm)  |
| Maximum Speed:                | 10000 RPM                        | Screw Finish:             | Black Oxide         |
| Parallel Misalignment:        | 0.30 mm                          | Bore Tolerance:           | +0.03 mm / -0.00 mm |
| Axial Motion:                 | 0.76 mm                          | ISO 9001:2015:            | Certified           |
| Bellows Attachment Method:    | Epoxy                            | REACH:                    | Compliant           |
| Length Tolerance:             | +/- 0.76 mm                      | RoHS3:                    | Compliant           |
| Recommended Hex Key:          | Metric Hex Keys                  | Conflict Minerals:        | Compliant           |
| B1 Min Shaft Penetration:     | 22.2 mm                          | Tariff Code:              | 8483.60.8000        |
| Temperature:                  | -40°F to 200°F (-40°C to 93°C)   | Number of Screws:         | 2                   |
| Product Group:                | Bellows Coupling Standard Length | Material:                 | Aluminum            |
| Shaft Tolerance:              | +0.000 mm / -0.013 mm            | B2 Min Shaft Penetration: | 22.2 mm             |

COMPONENT

Bellows Coupling Standard Length



Pacific International Bearing, Inc.  
33258 Central Ave, Union City, CA 94587  
1-800-228-8895, 510-512-7000,  
info@pibsales.com  
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

**MBCK80-35-30-A**  
**Ruland**  
35mm X 30mm Bores, 79.4mm, Od,  
96.9mm Length, Bellows Coupling With  
Keyways, High Stiffness, Aluminum

UNIT

Metric

SHEET