



|                               |                                    |                           |                     |
|-------------------------------|------------------------------------|---------------------------|---------------------|
| O.D. (D):                     | 1.000 in (25.4 mm)                 | Static Torque:            | 6.8 Nm              |
| Brand:                        | Ruland                             | Screw Material:           | Alloy Steel         |
| Dynamic Torque Reversing:     | 1.70 Nm                            | Bore Tolerance:           | +0.03 mm / -0.00 mm |
| Shaft Tolerance:              | +0.000 mm / -0.013 mm              | Material:                 | Aluminum            |
| Zero-Backlash?:               | Yes                                | Bore (B1):                | 11 mm               |
| Balanced Design:              | Yes                                | Bore (B2):                | 9 mm                |
| UNSPC:                        | 31163018                           | Keyway:                   | No                  |
| Cap Screw:                    | M3                                 | B1 Max Shaft Penetration: | 18.2 mm             |
| Dynamic Torque Non-Reversing: | 3.40 Nm                            | B2 Max Shaft Penetration: | 18.2 mm             |
| Hex Wrench Size:              | 2.5 mm                             | Seating Torque:           | 2.1 Nm              |
| Maximum Speed:                | 10000 RPM                          | Screw Finish:             | Black Oxide         |
| Torsional Stiffness:          | 20.9 Nm/Deg                        | Length (L):               | 1.523 in (38.7 mm)  |
| Angular Misalignment:         | 3.0 deg                            | ISO 9001:2015:            | Certified           |
| Parallel Misalignment:        | 0.20 mm                            | REACH:                    | Compliant           |
| Axial Motion:                 | 0.61 mm                            | RoHS3:                    | Compliant           |
| Bellows Attachment Method:    | Epoxy                              | Conflict Minerals:        | Compliant           |
| Length Tolerance:             | +/- 0.76 mm                        | Tariff Code:              | 8483.60.8000        |
| Temperature:                  | -40°F to 200°F (-40°C to 93°C)     | Number of Screws:         | 2 ea                |
| Product Group:                | Bellows Coupling - Extended Length | Recommended Hex Key:      | Metric Hex Keys     |

|           |                                    |
|-----------|------------------------------------|
| COMPONENT | Bellows Coupling - Extended Length |
|-----------|------------------------------------|



Pacific International Bearing, Inc.  
33258 Central Ave, Union City, CA 94587  
1-800-228-8895, 510-512-7000,  
info@pibsales.com  
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

**MBCL25-11-9-A**  
**Ruland**  
11mm X 9mm Bellows Coupling Bores,  
25.4mm Od., 38.7mm Length, Bellows  
Coupling, Clamp Style, Aluminum

UNIT

Metric

SHEET