



|                               |                                  |                           |                     |
|-------------------------------|----------------------------------|---------------------------|---------------------|
| O.D. (D):                     | 1.625 in (41.3 mm)               | Seating Torque:           | 4.6 Nm              |
| Brand:                        | Ruland                           | Bore Tolerance:           | +0.03 mm / -0.00 mm |
| Hex Wrench Size:              | 3.0 mm                           | Number of Screws:         | 2 ea                |
| Temperature:                  | -40°F to 200°F (-40°C to 93°C)   | Material:                 | Aluminum            |
| Product Group:                | Bellows Coupling Standard Length | Bore (B1):                | 16 mm               |
| Shaft Tolerance:              | +0.000 mm / -0.013 mm            | Bore (B2):                | 13 mm               |
| Zero-Backlash?:               | Yes                              | Keyway:                   | No                  |
| Balanced Design:              | Yes                              | B1 Max Shaft Penetration: | 24.0 mm             |
| UNSPC:                        | 31163018                         | Length (L):               | 2.316 in (58.8 mm)  |
| Maximum Speed:                | 10000 RPM                        | B2 Max Shaft Penetration: | 24.0 mm             |
| Cap Screw:                    | M4                               | Screw Material:           | Alloy Steel         |
| Dynamic Torque Non-Reversing: | 14.00 Nm                         | Screw Finish:             | Black Oxide         |
| Dynamic Torque Reversing:     | 7.00 Nm                          | ISO 9001:2015:            | Certified           |
| Torsional Stiffness:          | 39.4 Nm/Deg                      | REACH:                    | Compliant           |
| Angular Misalignment:         | 3.0 deg                          | RoHS3:                    | Compliant           |
| Parallel Misalignment:        | 0.38 mm                          | Conflict Minerals:        | Compliant           |
| Axial Motion:                 | 0.76 mm                          | Tariff Code:              | 8483.60.8000        |
| Bellows Attachment Method:    | Epoxy                            | Length Tolerance:         | +/- 0.76 mm         |
| Static Torque:                | 28.0 Nm                          |                           |                     |

|           |                                  |
|-----------|----------------------------------|
| COMPONENT | Bellows Coupling Standard Length |
|-----------|----------------------------------|



**Pacific International Bearing, Inc.**  
33258 Central Ave, Union City, CA 94587  
1-800-228-8895, 510-512-7000,  
info@pibsales.com  
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

**MBCL41-16-13-A**  
**Ruland**  
16mm X 13mm Bores, 41.3mm, Od, 58.8 Mm  
Length, Bellows Coupling, Increased  
Misalignment, Aluminum

|        |
|--------|
| UNIT   |
| Metric |
| SHEET  |