



O.D. (D):	1.000 in (25.4 mm)	Static Torque:	6.8 Nm
Brand:	Ruland	Number of Screws:	2 ea
Seating Torque:	2.1 Nm	Bore Tolerance:	+0.03 mm / -0.00 mm
Product Group:	Bellows Coupling - Extended Length	Material:	Aluminum
Shaft Tolerance:	+0.000 mm / -0.013 mm	Bore (B1):	12 mm
Zero-Backlash?:	Yes	Bore (B2):	8 mm
Balanced Design:	Yes	Keyway:	Yes
UNSPC:	31163018	Keyway (K1):	4 mm
Cap Screw:	M3	Keyway (K2):	2 mm
Hex Wrench Size:	2.5 mm	B2 Max Shaft Penetration:	18.2 mm
Dynamic Torque Reversing:	1.70 Nm	B1 Max Shaft Penetration:	18.2 mm
Dynamic Torque Non-Reversing:	3.40 Nm	Length (L):	1.523 in (38.7 mm)
Torsional Stiffness:	20.9 Nm/Deg	Screw Material:	Alloy Steel
Angular Misalignment:	3.0 deg	Screw Finish:	Black Oxide
Parallel Misalignment:	0.20 mm	ISO 9001:2015:	Certified
Axial Motion:	0.61 mm	REACH:	Compliant
Bellows Attachment Method:	Epoxy	RoHS3:	Compliant
Length Tolerance:	+/- 0.76 mm	Conflict Minerals:	Compliant
Maximum Speed:	10000 RPM	Tariff Code:	8483.60.8000
Temperature:	-40°F to 200°F (-40°C to 93°C)	Recommended Hex Key:	Metric Hex Keys

COMPONENT	Bellows Coupling - Extended Length
-----------	------------------------------------



Pacific International Bearing, Inc.
33258 Central Ave, Union City, CA 94587
1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

MBCLK25-12-8-A
Ruland
12mm X 8mm Bellows Coupling Bores,
25.4mm Od., 38.7mm Length, Bellows
Coupling, Clamp Style With Keyways,
Aluminum

UNIT
Metric
SHEET