



|                               |                                  |                           |                     |
|-------------------------------|----------------------------------|---------------------------|---------------------|
| O.D. (D):                     | 1.625 in (41.3 mm)               | Number of Screws:         | 2 ea                |
| Brand:                        | Ruland                           | B2 Max Shaft Penetration: | 24.0 mm             |
| Seating Torque:               | 4.6 Nm                           | Tariff Code:              | 8483.60.8000        |
| Maximum Speed:                | 10000 RPM                        | Material:                 | Aluminum            |
| Temperature:                  | -40°F to 200°F (-40°C to 93°C)   | Bore (B1):                | 19 mm               |
| Product Group:                | Bellows Coupling Standard Length | Bore (B2):                | 17 mm               |
| Shaft Tolerance:              | +0.000 mm / -0.013 mm            | Keyway:                   | Yes                 |
| Zero-Backlash?:               | Yes                              | Keyway (K1):              | 6 mm                |
| Balanced Design:              | Yes                              | Keyway (K2):              | 5 mm                |
| UNSPC:                        | 31163018                         | Length (L):               | 2.316 in (58.8 mm)  |
| Hex Wrench Size:              | 3.0 mm                           | B1 Max Shaft Penetration: | 24.0 mm             |
| Cap Screw:                    | M4                               | Bore Tolerance:           | +0.03 mm / -0.00 mm |
| Dynamic Torque Non-Reversing: | 14.00 Nm                         | Screw Material:           | Alloy Steel         |
| Dynamic Torque Reversing:     | 7.00 Nm                          | Screw Finish:             | Black Oxide         |
| Torsional Stiffness:          | 39.4 Nm/Deg                      | ISO 9001:2015:            | Certified           |
| Angular Misalignment:         | 3.0 deg                          | REACH:                    | Compliant           |
| Parallel Misalignment:        | 0.38 mm                          | RoHS3:                    | Compliant           |
| Axial Motion:                 | 0.76 mm                          | Conflict Minerals:        | Compliant           |
| Bellows Attachment Method:    | Epoxy                            | Length Tolerance:         | +/- 0.76 mm         |
| Static Torque:                | 28.0 Nm                          |                           |                     |

|           |                                  |
|-----------|----------------------------------|
| COMPONENT | Bellows Coupling Standard Length |
|-----------|----------------------------------|



Pacific International Bearing, Inc.  
33258 Central Ave, Union City, CA 94587  
1-800-228-8895, 510-512-7000,  
info@pibsales.com  
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

**MBCLK41-19-17-A**  
**Ruland**  
19mm X 17mm Bores, 41.3mm, Od, 58.8 Mm  
Length, Bellows Coupling With Keyways,  
Increased Misalignment, Aluminum

UNIT

Metric

SHEET