



|                     |                       |                             |                                 |
|---------------------|-----------------------|-----------------------------|---------------------------------|
| O.D. (D):           | 40 mm                 | Number of Screws:           | 1 ea                            |
| Brand:              | Ruland                | Screw Location (R):         | 14.73 mm                        |
| Material:           | Aluminum              | Seating Torque:             | 16 Nm                           |
| Bore (B1):          | 20 mm                 | Hex Wrench Size:            | 5.0 mm                          |
| Bore Tolerance:     | +0.050 mm / +0.012 mm | Temperature:                | -40°F to 225°F (-40°C to 107°C) |
| Screw Material:     | Alloy Steel           | Country of Origin:          | USA                             |
| Screw Finish:       | Black Oxide           | Finish Specification:       | Bright No Plating               |
| Forged Clamp Screw: | M6 x 16               | Shaft Tolerance:            | +0.000 mm / -0.013 mm           |
| ISO 9001:2015:      | Certified             | UNSPC:                      | 3162811                         |
| REACH:              | Compliant             | Clearance Diameter (C) MAX: | 47.4 mm                         |
| RoHS3:              | Compliant             | Material Specification:     | 2024-T351 Bar                   |
| Conflict Minerals:  | Compliant             | Width (W):                  | 15 mm                           |
| Tariff Code:        | 8483.60.8000          |                             |                                 |



Pacific International Bearing, Inc.  
33258 Central Ave, Union City, CA 94587  
1-800-228-8895, 510-512-7000,  
info@pibsales.com  
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

COMPONENT

Shaft Collar - One-Piece

MCL-20-A

Ruland

20mm Bore; 40mm Od, 15mm Width, One-piece Shaft Collar, Aluminum, Clamp Style

UNIT

Metric

SHEET