



|                     |                                 |                             |                                |
|---------------------|---------------------------------|-----------------------------|--------------------------------|
| O.D. (D):           | 57 mm                           | Number of Screws:           | 1 ea                           |
| Brand:              | Ruland                          | Screw Location (R):         | 23.24 mm                       |
| Material:           | Anodized Aluminum               | Seating Torque:             | 9.6 Nm                         |
| Bore (B1):          | 34 mm                           | Hex Wrench Size:            | 5.0 mm                         |
| Bore Tolerance:     | +0.050 mm / +0.012 mm           | Temperature:                | -40°F to 200°F (-40°C to 93°C) |
| Screw Material:     | 18-8 300 Series Stainless Steel | Country of Origin:          | USA                            |
| Screw Finish:       | Bright                          | Finish Specification:       | Anodize                        |
| Forged Clamp Screw: | M6 x 18                         | Shaft Tolerance:            | +0.000 mm / -0.013 mm          |
| ISO 9001:2015:      | Certified                       | UNSPC:                      | 31162811                       |
| REACH:              | Compliant                       | Clearance Diameter (C) MAX: | 62.4 mm                        |
| RoHS3:              | Compliant                       | Material Specification:     | 2024-T351 Bar                  |
| Conflict Minerals:  | Compliant                       | Width (W):                  | 15 mm                          |
| Tariff Code:        | 8483.60.8000                    |                             |                                |

COMPONENT

Shaft Collar - One-Piece



Pacific International Bearing, Inc.  
33258 Central Ave, Union City, CA 94587  
1-800-228-8895, 510-512-7000,  
info@pibsales.com  
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

MCL-34-AN  
Ruland  
34mm Bore; 57mm Od, 15mm Width, One-piece Shaft Collar, Anodized Aluminum, Clamp Style

UNIT

Metric

SHEET