



O.D. (D):	16 mm	Number of Screws:	1 ea
Brand:	Ruland	Screw Location (R):	5.51 mm
Material:	Black Oxide Steel	Seating Torque:	2.1 Nm
Bore (B1):	5 mm	Hex Wrench Size:	2.5 mm
Bore Tolerance:	+0.050 mm / +0.012 mm	Temperature:	-40°F to 350°F (-40°C to 176°C)
Screw Material:	Alloy Steel	Country of Origin:	USA
Screw Finish:	Black Oxide	Finish Specification:	Black Oxide
Forged Clamp Screw:	M3 x 8	Shaft Tolerance:	+0.000 mm / -0.013 mm
ISO 9001:2015:	Certified	UNSPC:	3162811
REACH:	Compliant	Clearance Diameter (C) MAX:	20.8 mm
RoHS3:	Compliant	Material Specification:	1215 Bar
Conflict Minerals:	Compliant	Width (W):	9 mm
Tariff Code:	8483.60.8000		



Pacific International Bearing, Inc.
33258 Central Ave, Union City, CA 94587
1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

COMPONENT	Shaft Collar - One-Piece	
MCL-5-F Ruland 5mm Bore; 16mm Od, 9mm Width, One-piece Shaft Collar, Black Oxide Steel, Clamp Style	UNIT	
	Metric	
	SHEET	