



O.D. (D):	82 mm	Number of Screws:	1 ea
Brand:	Ruland	Screw Location (R):	34.24 mm
Material:	303 Stainless Steel	Seating Torque:	23 Nm
Bore (B1):	54 mm	Hex Wrench Size:	6.0 mm
Bore Tolerance:	+0.050 mm / +0.012 mm	Temperature:	-40°F to 350°F (-40°C to 176°C)
Screw Material:	18-8 300 Series Stainless Steel	Country of Origin:	USA
Screw Finish:	Bright	Finish Specification:	Bright No Plating
Forged Clamp Screw:	M8 x 25	Shaft Tolerance:	+0.000 mm / -0.013 mm
ISO 9001:2015:	Certified	UNSPC:	31162811
REACH:	Compliant	Clearance Diameter (C) MAX:	88.8 mm
RoHS3:	Compliant	Material Specification:	303 Stainless Steel
Conflict Minerals:	Compliant	Width (W):	19 mm
Tariff Code:	8483.60.8000		



Pacific International Bearing, Inc.
 33258 Central Ave, Union City, CA 94587
 1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

COMPONENT	Shaft Collar - One-Piece	
MCL-54-SS Ruland 54mm Bore; 82mm Od, 19mm Width, One-piece Shaft Collar, 303 Stainless Steel, Clamp Style	UNIT	
	Metric	
	SHEET	