



O.D. (D):	40 mm	Material:	Aluminum
Brand:	Ruland	Tariff Code:	8483.60.8000
Screw Location (R):	14.73 mm	Conflict Minerals:	Compliant
Material Specification:	2024-T351 Bar	RoHS3:	Compliant
Clearance Diameter (C) MAX:	47.4 mm	REACH:	Compliant
UNSPC:	31162811	ISO 9001:2015:	Certified
Shaft Tolerance:	+0.000 mm / -0.013 mm	Forged Clamp Screw:	M6 x 16
Finish Specification:	Bright No Plating	Screw Finish:	Black Oxide
Country of Origin:	USA	Screw Material:	Alloy Steel
Temperature:	-40°F to 225°F (-40°C to 107°C)	Bore Tolerance:	+0.050 mm / +0.012 mm
Hex Wrench Size:	5.0 mm	Bore (B1):	20 mm
Seating Torque:	16 Nm	Width (W):	15 mm
Number of Screws:	1 ea		

COMPONENT	Shaft Collar - D-Bore
-----------	-----------------------



Pacific International Bearing, Inc.
 33258 Central Ave, Union City, CA 94587
 1-800-228-8895, 510-512-7000,
 info@pibsales.com
 www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

MCLD-20-A Ruland 20mm Bore; 40mm Od, 15mm Width, D-bore Shaft Collar, Aluminum, One-piece, Clamp Style	UNIT
	Metric
	SHEET