



| | | | |
|-------------------------------|------------------------------|---------------------------|---------------------------------|
| O.D. (D): | 25 mm | Seating Torque: | 3.20 Nm |
| Brand: | Ruland | Screw Material: | 18-8 300 Series Stainless Steel |
| Hex Wrench Size: | 2.5 mm | Number of Screws: | 4 |
| Country of Origin: | Ireland | Material: | Aluminum |
| Finish Specification: | SurTec 650 | Bore (B1): | 9 mm |
| Zero-Backlash?: | Yes | Bore (B2): | 9 mm |
| Forged Set Screw: | M5 | B1 Max Shaft Penetration: | 9.6 mm |
| Balanced Design: | Yes | B2 Max Shaft Penetration: | 9.6 mm |
| UNSPC: | 31163003 | Length (L): | 34.0 mm |
| Maximum Speed: | 12000 RPM | Bore Tolerance: | +0.020 mm / +0.000 mm |
| Dynamic Torque Non-Reversing: | 3.10 Nm | Screw Finish: | Bright |
| Torsional Stiffness: | 3.8 Nm/Deg | ISO 9001:2015: | Certified |
| Angular Misalignment: | 3.0 deg | REACH: | Compliant |
| Parallel Misalignment: | 0.40 mm | RoHS3: | Compliant |
| Axial Motion: | 0.70 mm | Conflict Minerals: | Compliant |
| Peak Torque: | 5.20 Nm | Tariff Code: | 8483.60.8000 |
| Moment of Inertia: | 0.0107751 lb-in ² | Material Specification: | 7075-T651 Bar |
| Dynamic Torque Reversing: | 2.05 Nm | | |

COMPONENT

Slit Coupling



Pacific International Bearing, Inc.
33258 Central Ave, Union City, CA 94587
1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

MRLS25-9-9-A
Ruland
9mm X 9mm Long Slit Coupling, 25.0mm
Od, 34.0mm Length, Aluminum, Set Screw
Style

| |
|--------|
| UNIT |
| Metric |
| SHEET |