



|                               |                                                  |                           |                                                  |
|-------------------------------|--------------------------------------------------|---------------------------|--------------------------------------------------|
| O.D. (D):                     | 1.181 in (30.0 mm)                               | Seating Torque:           | 4.6 Nm                                           |
| Brand:                        | Ruland                                           | Length (L):               | 1.496 in (38.0 mm)                               |
| UNSPC:                        | 31163003                                         | B2 Max Shaft Penetration: | 0.717 in (18.2 mm)                               |
| Temperature:                  | -40°F to 350°F (-40°C to 176°C)                  | Material:                 | 303 Stainless Steel                              |
| Country of Origin:            | USA                                              | Bore (B1):                | 12 mm                                            |
| Product Group:                | 4 Beam Couplings Clamp                           | Bore (B2):                | 0.3750 in                                        |
| Shaft Tolerance:              | +0.0000 in / -0.0005 in<br>+0.000 mm / -0.013 mm | Keyway:                   | No                                               |
| Zero-Backlash?:               | Yes                                              | B1 Max Shaft Penetration: | 0.717 in (18.2 mm)                               |
| Balanced Design:              | Yes                                              | Bore Tolerance:           | +0.001 in / -0.000 in<br>(+0.025 mm / -0.000 mm) |
| Cap Screw:                    | M4                                               | Number of Screws:         | 2 ea                                             |
| Hex Wrench Size:              | 3.0 mm                                           | Screw Material:           | Alloy Steel                                      |
| Static Torque:                | 10.00 Nm                                         | Screw Finish:             | Black Oxide                                      |
| Dynamic Torque Non-Reversing: | 5.00 Nm                                          | ISO 9001:2015:            | Certified                                        |
| Dynamic Torque Reversing:     | 2.50 Nm                                          | REACH:                    | Compliant                                        |
| Torsional Stiffness:          | 0.46 Deg/Nm                                      | RoHS3:                    | Compliant                                        |
| Angular Misalignment:         | 3.0 deg                                          | Conflict Minerals:        | Compliant                                        |
| Parallel Misalignment:        | 0.38 mm                                          | Tariff Code:              | 8483.60.8000                                     |
| Maximum Speed:                | 6000 RPM                                         | Axial Motion:             | 0.25 mm                                          |

|           |                              |
|-----------|------------------------------|
| COMPONENT | MW Series Four Beam Coupling |
|-----------|------------------------------|



Pacific International Bearing, Inc.  
33258 Central Ave, Union City, CA 94587  
1-800-228-8895, 510-512-7000,  
info@pibsales.com  
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

**MWC30-12MM-3/8"-SS**  
**Ruland**  
12mm X 3/8" Bores, 1.181" (30.0mm) Od  
1.496" (38.0mm) Length, Four Beam  
Coupling, Stainless Steel Set Screw Style

|             |
|-------------|
| UNIT        |
| Inch/Metric |
| SHEET       |