



O.D. (D):	1.181 in (30.0 mm)	Number of Screws:	4 ea
Brand:	Ruland	Length (L):	1.181 in (30.0 mm)
Forged Set Screw:	M5	B2 Max Shaft Penetration:	0.559 in (14.2 mm)
Maximum Speed:	6000 RPM	Material:	Aluminum
Temperature:	-40°F to 225°F (-40°C to 107°C)	Bore (B1):	0.3750 in
Country of Origin:	USA	Bore (B2):	0.3750 in
Product Group:	4 Beam Couplings Set Screw	Keyway:	No
Shaft Tolerance:	+0.0000 in / -0.0005 in	B1 Max Shaft Penetration:	0.559 in (14.2 mm)
Zero-Backlash?:	Yes	Bore Tolerance:	+0.001 in / -0.000 in (+0.025 mm / -0.000 mm)
UNSPC:	31163003	Tariff Code:	8483.60.8000
Seating Torque:	4 Nm	Screw Material:	Alloy Steel
Static Torque:	6.90 Nm	Screw Finish:	Black Oxide
Dynamic Torque Non-Reversing:	3.45 Nm	ISO 9001:2015:	Certified
Dynamic Torque Reversing:	1.73 Nm	REACH:	Compliant
Torsional Stiffness:	0.71 Deg/Nm	RoHS3:	Compliant
Angular Misalignment:	3.0 deg	Conflict Minerals:	Compliant
Parallel Misalignment:	0.38 mm	Axial Motion:	0.25 mm
Hex Wrench Size:	2.5 mm		

COMPONENT	MW Series Four Beam Coupling
-----------	------------------------------



Pacific International Bearing, Inc.
33258 Central Ave, Union City, CA 94587
1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

MWS30-3/8"-3/8"-A
Ruland
3/8" X 3/8" Bores, 1.181" (30.0mm) Od 1.181"
(30.0mm) Length, Four Beam Coupling,
Aluminum Set Screw Style

UNIT

Inch

SHEET