|   |  |  | "balls<br>250 - F  |              |       |
|---|--|--|--|--------------|-------|
| Bore Diameter (d) 7.9998 in                                   |  |  |  |              |       |
| Outside Diameter (D)<br>Width (B)                             | 8.5003 in<br>.2500 in  | $F = .025^{3}$   |  |              |       |
| Closure   | Corrosion Resistant Plated   |  |  |              |       |
| Ring Material   Corrosion Resistant Plated     Brand   KAYDON |  |  |  |              |       |
|   |  |  |  |              |       |
| L2  | 8.3140 in  |  | COMPONENT  | Thin Section | n     |
| P   | Pacific International Bearing, Inc.<br>33258 Central Ave, Union City, CA 94587<br>1-800-228-8895, 510-512-7000,<br>info@pibsales.com<br>www.pibsales.com | This file and any associated information<br>and specifications are provided for<br>reference and evaluation purposes only,<br>and is subject to change without notice. PIB<br>makes no representations, warranties or<br>guarantees as to the appropriateness,<br>accuracy, completeness, or suitability for<br>any purpose, of the file, information or | NA080XP0<br>KAYDON<br>7.9998in X 8.5003in X .2500in, Thin Section<br>Bearings, Four Point Contact Type-x,<br>Endurakote Anti-corrosion, Open |              | UNIT  |
|   |  |  |  |              | Inch  |
|   |  | specifications. You are solely responsible<br>for the use of the file, information or<br>specifications.   |  |              | SHEET |