


$$F = .060^4$$

|                      |                            |
|----------------------|----------------------------|
| Bore Diameter (d)    | 3.9998 in                  |
| Outside Diameter (D) | 5.0003 in                  |
| Width (B)            | .5000 in                   |
| Closure              | Open                       |
| Ring Material        | Corrosion Resistant Plated |
| Ball Material        | Corrosion Resistant Plated |
| Brand                | KAYDON                     |
| L1                   | 4.3700 in                  |
| L2                   | 4.6300 in                  |

|           |              |
|-----------|--------------|
| COMPONENT | Thin Section |
|-----------|--------------|

|   |   |  |  |       |
|---|---|--|--|-------|
|  | <b>Pacific International Bearing, Inc.</b><br>33258 Central Ave, Union City, CA 94587<br>1-800-228-8895, 510-512-7000,<br>info@pibsales.com<br>www.pibsales.com | This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications. | <b>ND040AR0</b><br><b>KAYDON</b><br>3.9998in X 5.0003in X .5000in, Thin Section<br>Bearing, Angular Contact Type A,<br>Endurakote Anti-corrosion, Open | UNIT  |
|   |   |  |  | Inch  |
|   |   |  |  | SHEET |