D F <sub>w</sub>	C		$D_1 d_w + F_w D$			
Width (B) 23		23 mm				
Brand INA		INA				
Dynamic Load(Cr) 2		2270.57 lbs				
Dynamic Load AxialCA		2315.53 lbs				
Static Load Axial ca		3462.06 lbs				
Speed Limit (RPM)		11000				
Bore Diameter (d)		12 mm				
Static Load Cap (C0r)		2472.9 lbs	1	COMPONENT Needle Roller Axial Ball Bearings		ial Ball
0.D. (D)		21 mm	]			
	Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com		This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.	UNIT INA 12mm X 21mm X 23mm, Needle Roller, Axial Ball Bearing, Single Direction, No End Cap, For Oil Lubrication SHEET		UNIT
<b><b>ÝIB</b></b>						Metric
						SHEET