



O.D. (D):	0.625 in (15.9 mm)	Seating Torque:	0.6 Nm
Brand:	Ruland	Bore Tolerance:	+0.025 mm / -0.000 mm
UNSPC:	31163003	Material:	Aluminum
Temperature:	-40°F to 225°F (-40°C to 107°C)	Bore (B1):	4 mm
Country of Origin:	USA	Bore (B2):	3 mm
Product Group:	P-Series 4 Beam Couplings Clamp	Keyway:	No
Shaft Tolerance:	+0.000 mm / -0.013 mm	B1 Max Shaft Penetration:	9.6 mm
Zero-Backlash?:	Yes	B2 Max Shaft Penetration:	9.6 mm
Balanced Design:	Yes	Screw Material:	Alloy Steel
Cap Screw:	M2	Number of Screws:	2 ea
Hex Wrench Size:	1.5 mm	Screw Finish:	Black Oxide
Static Torque:	1.36 Nm	ISO 9001:2015:	Certified
Dynamic Torque Non-Reversing:	0.68 Nm	REACH:	Compliant
Dynamic Torque Reversing:	0.34 Nm	RoHS3:	Compliant
Torsional Stiffness:	4.78 Deg/Nm	Conflict Minerals:	Compliant
Angular Misalignment:	3.0 deg	Tariff Code:	8483.60.8000
Parallel Misalignment:	0.20 mm	Axial Motion:	0.13 mm
Maximum Speed:	6000 RPM		

COMPONENT

P-Series Four Beam Coupling



Pacific International Bearing, Inc.
33258 Central Ave, Union City, CA 94587
1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

PCMR16-4-3-A
Ruland
4mm X 3mm Bores, 15.9mm Od, 20.3mm
Length, Four Beam Coupling, Aluminum
Clamp Style

UNIT

Metric

SHEET