



O.D. (D):	1.250 in (31.8 mm)	Seating Torque:	4.6 Nm
Brand:	Ruland	Screw Material:	Alloy Steel
Hex Wrench Size:	3.0 mm	Number of Screws:	2 ea
Temperature:	-40°F to 225°F (-40°C to 107°C)	Material:	Aluminum
Country of Origin:	USA	Bore (B1):	0.3750 in
Product Group:	P-Series 4 Beam Couplings Clamp	Bore (B2):	0.3125 in
Shaft Tolerance:	+0.0000 in / -0.0005 in	Keyway:	No
Zero-Backlash?:	Yes	B1 Max Shaft Penetration:	0.695 in
Balanced Design:	Yes	B2 Max Shaft Penetration:	0.695 in
Maximum Speed:	6000 RPM	Bore Tolerance:	+0.001 in / -0.000 in
UNSPC:	31163003	Screw Finish:	Black Oxide
Static Torque:	60 lb-in	ISO 9001:2015:	Certified
Dynamic Torque Non-Reversing:	30 lb-in	REACH:	Compliant
Dynamic Torque Reversing:	15 lb-in	RoHS3:	Compliant
Torsional Stiffness:	0.070 Deg/lb-in	Conflict Minerals:	Compliant
Angular Misalignment:	3.0 deg	Tariff Code:	8483.60.8000
Parallel Misalignment:	0.015 in	Axial Motion:	0.010 in
Cap Screw:	M4		

COMPONENT	P-Series Four Beam Coupling
-----------	-----------------------------



Pacific International Bearing, Inc.
33258 Central Ave, Union City, CA 94587
1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

PCR20-6-5-A
Ruland
3/8" X 5/16" Bores, 1.250" Od, 1.500"
Length, Four Beam Coupling, Aluminum
Clamp Style

UNIT
Inch
SHEET