



O.D. (D):	0.375 in (9.5 mm)	Number of Screws:	2 ea
Brand:	Ruland	Tariff Code:	8483.60.8000
Seating Torque:	0.29 Nm	Conflict Minerals:	Compliant
Parallel Misalignment:	0.008 in (0.20 mm)	RoHS3:	Compliant
Angular Misalignment:	3.0 deg	REACH:	Compliant
Torsional Stiffness:	1.337 Deg/lb-in (11.83 Deg/Nm)	ISO 9001:2015:	Certified
Dynamic Torque Reversing:	1.4 lb-in (0.16 Nm)	Screw Finish:	Black Oxide
Dynamic Torque Non-Reversing:	2.7 lb-in (0.31 Nm)	Screw Material:	Alloy Steel
Static Torque:	5.5 lb-in (0.62 Nm)	Bore Tolerance:	+0.001 in / -0.000 in (+0.025 mm / -0.000 mm)
Cap Screw:	M1.6	B2 Max Shaft Penetration:	0.265 in (6.7 mm)
UNSPC:	31163003	B1 Max Shaft Penetration:	0.265 in (6.7 mm)
Shaft Tolerance:	+0.0000 in / -0.0005 in +0.000 mm / -0.013 mm	Keyway:	No
Product Group:	P-Series 4 Beam Couplings Clamp	Bore (B2):	0.0938 in
Country of Origin:	USA	Bore (B1):	3 mm
Temperature:	-40°F to 225°F (-40°C to 107°C)	Material:	Aluminum
Maximum Speed:	6000 RPM	Axial Motion:	0.005 in (0.13 mm)
Hex Wrench Size:	1.5 mm		

COMPONENT	P-Series Four Beam Coupling
-----------	-----------------------------



Pacific International Bearing, Inc.
33258 Central Ave, Union City, CA 94587
1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

PCR6-3MM-3/32"-A
Ruland
3mm X 3/32" Bores, 0.375" Od, 0.563"
Length, Four Beam Coupling, Aluminum
Set Screw Style

UNIT
Inch/Metric
SHEET