



O.D. (D):	0.375 in (9.5 mm)	Number of Screws:	2 ea
Brand:	Ruland	Tariff Code:	8483.60.8000
Seating Torque:	0.21 Nm	Conflict Minerals:	Compliant
Parallel Misalignment:	0.20 mm	RoHS3:	Compliant
Angular Misalignment:	3.0 deg	REACH:	Compliant
Torsional Stiffness:	11.83 Deg/Nm	ISO 9001:2015:	Certified
Dynamic Torque Reversing:	0.16 Nm	Screw Finish:	Black Oxide
Dynamic Torque Non-Reversing:	0.31 Nm	Screw Material:	Alloy Steel
Static Torque:	0.62 Nm	Bore Tolerance:	+0.025 mm / -0.000 mm
UNSPC:	31163003	B2 Max Shaft Penetration:	6.7 mm
Forged Set Screw:	M2	B1 Max Shaft Penetration:	6.7 mm
Shaft Tolerance:	+0.000 mm / -0.013 mm	Keyway:	No
Product Group:	P-Series 4 Beam Couplings Set Screw	Bore (B2):	3 mm
Country of Origin:	USA	Bore (B1):	3 mm
Temperature:	-40°F to 225°F (-40°C to 107°C)	Material:	Aluminum
Maximum Speed:	6000 RPM	Axial Motion:	0.13 mm
Hex Wrench Size:	0.9 mm		

COMPONENT

P-Series Four Beam Coupling



Pacific International Bearing, Inc.
33258 Central Ave, Union City, CA 94587
1-800-228-8895, 510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

PSMR10-3-3-A
Ruland
3mm X 3mm Bores, 9.5mm Od, 14.3mm
Length, Four Beam Coupling, Aluminum
Clamp Style

UNIT

Metric

SHEET