


| Bore Diameter (d) | 0.5 in |
|----------------------|-------------------------|
| Outside Diameter (D) | 1.125 in |
| Width (B) | 0.3125 in |
| Closure | Rubber Seal Non-Contact |
| Ring Material | 52100 Chrome Steel |
| Ball Material | 52100 Chrome Steel |
| Brand | TPI |
| Precision | Abec 1 |
| Radial Clearance | C3 |
| Lubrication | L627 Polyrex EM Grease |
| Dynamic Load(Cr) | 1146.53 lbs |
| Static Load(COr) | 537.29 lbs |



Non-contact sealed type (LLB)

| PIB |
|-----|
| |

Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

COMPONENT

INCH SERIES SEALED

R8-LLB-C3/L627

TPI

0.5 In X 1.125 In X 0.3125 In, Single Row Radial, Deep Groove Ball Bearing, Two Non-contact Rubber Seals UNIT

INCH

SHEET