


Bore Diameter (d)	0.5 in
Outside Diameter (D)	1.125 in
Width (B)	0.3125 in
Closure	Rubber Seal Contact
Ring Material	52100 Chrome Steel
Ball Material	52100 Chrome Steel
Brand	TPI
Precision	Abec 1
Radial Clearance	Normal
Lubrication	2AS Shell Alvania Grease S2
Dynamic Load(Cr)	1146.53 lbs
Static Load(C0r)	537.29 lbs
Note	Dust/Water Resistant Seal



Contact sealed type (LLU)

COMPONENT

PIB

Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

R8-LLU/2AS

TPI

0.5 In X 1.125 In X 0.3125 In, Single Row Radial, Deep Groove Ball Ball Bearing, Two Contact Rubber Seals UNIT

INCH SERIES SEALED

INCH

SHEET