


Bore Diameter (d)	.1250 in
Outside Diameter (D)	.2500 in
Width (B)	.1094 in
Closure	Metallic Shield
Ring Material	52100 Chrome Steel
Ball Material	52100 Chrome Steel
Brand	ИМВ
Precision	ABEC 5
Radial Clearance	P24
Flanged	Flanged
Lubrication	LY121 Kyodo Yushi SRL Grease
Dynamic Load(Cr)	64 lbs
Static Load(C0r)	22 lbs
Note	MT - Noise Sensitive App.
Series	RIF



COMPONENT

**INCH SERIES SHIELDED** 



## Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

## RIF418-ZZMTRP5P24LY121

## **NMB**

.1250in X .2500in X .1094in, Miniature Instrument Deep, Groove Radial Ball Bearing, Two Metal Shields, Flanged UNIT

INCH

**SHEET**