



Brand:	Ruland	Length (L):	0.787 in (20.0 mm)
Dynamic Torque Non-Reversing:	6.2 lb-in (0.70 Nm)	Bore Tolerance:	+0.001 in / -0.000 in (+0.020 mm / -0.000 mm)
Country of Origin:	Ireland	O.D. (D):	0.512 in (13.0 mm)
Finish Specification:	SurTec 650	Material:	Aluminum
Zero-Backlash?:	Yes	Bore (B1):	0.1875 in
Forged Set Screw:	M2.5	Bore (B2):	3 mm
Balanced Design:	Yes	B1 Max Shaft Penetration:	0.276 in (7.0 mm)
UNSPC:	31163003	B2 Max Shaft Penetration:	0.276 in (7.0 mm)
Dynamic Torque Reversing:	4.4 lb-in (0.50 Nm)	Screw Material:	18-8 300 Series Stainless Steel
Hex Wrench Size:	1.3 mm	Number of Screws:	4
Torsional Stiffness:	8.0 lb-in/Deg (0.9 Nm/Deg)	Screw Finish:	Bright
Angular Misalignment:	2.5 deg	ISO 9001:2015:	Certified
Parallel Misalignment:	0.006 in (0.15 mm)	REACH:	Compliant
Axial Motion:	0.012 in (0.30 mm)	RoHS3:	Compliant
Peak Torque:	10.6 in-lb (1.20 Nm)	Conflict Minerals:	Compliant
Moment of Inertia:	0.0004566 lb-in²	Tariff Code:	8483.60.8000
Maximum Speed:	20000 RPM	Material Specification:	7075-T651 Bar
Seating Torque:	0.44 Nm		

COMPONENT	Slit Coupling
-----------	---------------



Pacific International Bearing, Inc.  
33258 Central Ave, Union City, CA 94587  
1-800-228-8895, 510-512-7000,  
info@pibsales.com  
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

**RLS8-3/16"-3MM-A**  
**Ruland**  
0.188" X 3mm Long Slit Coupling, 0.512"  
(13.0mm) Od, 0.778" (20.0mm) Length,  
Aluminum, Set Screw Style

UNIT
Inch/Metric
SHEET