




Brand	Ruland
Seating Torque	0.21 Nm
Material	Aluminum
Bore (B1)	0.1250 in
Bore (B2)	3 mm
B1 Max Shaft Penetration	0.276 in (7.0 mm)
B2 Max Shaft Penetration	0.276 in (7.0 mm)
Screw Material	18-8 300 Series Stainless Steel
Screw Finish	Bright
Bore Tolerance	+0.001 in / -0.000 in (+0.020 mm / -0.000 mm)
ISO 9001:2015	Certified
REACH	Compliant
RoHS3	Compliant
Conflict Minerals	Compliant
Tariff Code	8483.60.8000
Number of Screws	2
O.D. (D)	0.512 in (13.0 mm)
Length (L)	0.661 in (16.8 mm)
Dynamic Torque Non-Reversing	4.9 lb-in (0.55 Nm)
Dynamic Torque Reversing	3.1 lb-in (0.35 Nm)
Finish Specification	SurTec 650
Zero-Backlash?	Yes
Balanced Design	Yes
UNSPC	31163003
Clearance Diameter (C) MAX	0.571 in (14.5 mm)
Cap Screw	M1.6
Maximum Speed	12000 RPM
Hex Wrench Size	1.5 mm
Torsional Stiffness	7.0 lb-in/Deg (0.8 Nm/Deg)
Angular Misalignment	2.5 deg
Parallel Misalignment	0.003 in (0.08 mm)
Axial Motion	0.012 in (0.30 mm)
Peak Torque	7.1 in-lb (0.80 Nm)
Moment of Inertia	0.0003681 lb-in²
Country of Origin	Ireland
Material Specification	7075-T651 Bar



COMPONENT

Slit Coupling



Pacific International Bearing, Inc.
33258 Central Ave, Union City, CA 94587 1-800-228-8895,
510-512-7000,
info@pibsales.com
www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

RSC8-1/8"-3MM-A
Ruland
0.125" X 3mm Short Slit Coupling, 0.512" (13.0mm) Od, 0.661"
(16.8mm) Length, Aluminum, Clamp Style

UNIT
Inch/Metric
SHEET