


| | |
|-------------------|---------------------------|
| Width (B) | 15 mm |
| Closure | Rubber Seal Non-Contact |
| Ring Material | Stainless Steel |
| Ball Material | AISI 440C Stainless Steel |
| Brand | FAG |
| Radial Clearance | Normal |
| Bore Diameter (d) | 25 mm |
| Series | 6205 |
| O.D. (D) | 52 mm |

| | |
|-----------|----------------------|
| COMPONENT | METRIC SERIES SEALED |
|-----------|----------------------|

| | | | | |
|---|---|--|---|--------|
|  | Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com | This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications. | S6205-2RSR-HLC FAG 25 Mm X 52 Mm X 15 Mm, Single Row Radial, Deep Groove Ball Bearing, Two Non Contact Rubber Seals | UNIT |
| | | | | METRIC |
| | | | | SHEET |