| ×                  |                                                                                              | _                                               |                                                                                |                     |       |
|--------------------|----------------------------------------------------------------------------------------------|-------------------------------------------------|--------------------------------------------------------------------------------|---------------------|-------|
| Width (B)          | 36 mm                                                                                        |                                                 |                                                                                |                     |       |
| Contact Angle      | 15° high-speed E design                                                                      |                                                 |                                                                                |                     |       |
| Bearing Arrangemen | t Pair - Universal Matched                                                                   |                                                 |                                                                                |                     |       |
| Brand              | SKF                                                                                          |                                                 |                                                                                |                     |       |
| Precision          | P4A                                                                                          |                                                 |                                                                                |                     |       |
| Ring Material      | Chrome Steel 100Cr6                                                                          |                                                 |                                                                                |                     |       |
| Ball Material      | Ceramic Si3N4                                                                                |                                                 |                                                                                |                     |       |
| Preload            | Light Preload                                                                                |                                                 |                                                                                |                     |       |
| Dynamic Load(Cr)   | 6118 lbs                                                                                     |                                                 |                                                                                |                     |       |
| Closure            | Rubber Seal                                                                                  |                                                 |                                                                                |                     |       |
|                    | Pacific International Bearing, In                                                            | and is subject to change without hotice. I ib j | S7011 CE/HCP4ADGA                                                              |                     | UNIT  |
| <b><b>PIB</b></b>  | 33258 Central Ave, Union City, CA 9458<br>1-800-228-8895, 510-512-7000,<br>info@pibsales.com |                                                 | SI<br>55mm X 90mm X 36n                                                        | m, Super Precision, |       |
|                    | www.pibsales.com                                                                             |                                                 | Angular Contact Bearing, 15° High-<br>speed E Design, Pair - Universal Matched |                     | SHEET |