| × | | | 1 | | | |
|--------------------|---------------------------------|---|--|--------------------|----------------------------|-------|
| Width (B) | 20 mn | n | | | | |
| Contact Angle | 25° hij | gh-speed E design | | | | |
| Bearing Arrangemen | t Single | e - Universal Matched | | | | |
| Brand | SKF | | | | | |
| Precision | P4A | | | | | |
| Ring Material | Chron | ne Steel 100Cr6 | | | | |
| Ball Material | Ceran | nic Si3N4 | | | | |
| Preload | Light | Preload | | | | |
| Dynamic Load(Cr) | 50581 | lbs | | | | |
| Closure | Rubbe | er Seal | | COMPONENT | | |
| | | ernational Bearing, Inc. | This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for | S7014 ACEGA/HCP4A | | UNIT |
| PIB | 33258 Centra 1-800-22 inf | al Ave, Union City, CA 94587 28-8895, 510-512-7000, fo@pibsales.com | | 70mm X 110mm X 20r | | |
| | www.pibsales.com | | any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications. | speed E Design, S | Single - Universal ched | SHEET |