


|                            | 1                               |  |  |
|----------------------------|---------------------------------|--|--|
| 0.D. (D)                   | 5/8 in                          |  |  |
| Tariff Code                | 8483.60.8000                    |  |  |
| Bore (B1)                  | 0.2500 in                       |  |  |
| Bore Tolerance             | +0.0020 in / +0.0005 in         |  |  |
| Screw Material             | Alloy Steel                     |  |  |
| Screw Finish               | Black Oxide                     |  |  |
| Forged Clamp Screw         | #4-40                           |  |  |
| ISO 9001:2015              | Certified                       |  |  |
| REACH                      | Compliant                       |  |  |
| RoHS3                      | Compliant                       |  |  |
| Conflict Minerals          | Compliant                       |  |  |
| Material                   | Black Oxide Steel               |  |  |
| Screw Location (R)         | 0.210 in                        |  |  |
| Number of Screws           | 2 ea                            |  |  |
| Seating Torque             | 15 lb-in                        |  |  |
| Hex Wrench Size            | 3/32 in                         |  |  |
| Temperature                | -40°F to 350°F (-40°C to 176°C) |  |  |
| Country of Origin          | USA                             |  |  |
| Finish Specification       | Black Oxide                     |  |  |
| Shaft Tolerance            | +0.0000 in / -0.0005 in         |  |  |
| UNSPC                      | 31162811                        |  |  |
| Clearance Diameter (C) MAX | 0.773 in                        |  |  |
| Material Specification     | 1215 Bar                        |  |  |
| Brand                      | Ruland                          |  |  |





Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

## SPD-4-F

## Ruland

0.2500in Bore; 0.6250in Od, 0.281in Width, D-bore Shaft Collar, Black Oxide Steel, One-piece, Clamp Style

Inch

SHEET