| ×                 |  | 1            | 1  |  |  |       |
|-------------------|--|--------------|--|--|--|-------|
| Width (B)         |  | 46 mm        | ×  |  |  |       |
| Width (C)         |  | 39 mm        |  |  |  |       |
| Width Total (T)   |  | 47 mm        |  |  |  |       |
| Brand             |  | FAG          |  |  |  |       |
| Dynamic Load(Cr)  |  | 67442.68 lbs |  |  |  |       |
| Speed Limit (RPM) |  | 4100         |  | COMPONENT  |  |       |
|                   | Pacific International Bearing, Inc.<br>33258 Central Ave, Union City, CA 94587<br>1-800-228-8895, 510-512-7000,<br>info@pibsales.com<br>www.pibsales.com |              | This file and any associated information<br>and specifications are provided for<br>reference and evaluation purposes only,<br>and is subject to change without notice. PIB<br>makes no representations, warranties or<br>guarantees as to the appropriateness,<br>accuracy, completeness, or suitability for<br>any purpose, of the file, information or<br>specifications. You are solely responsible<br>for the use of the file, information or<br>specifications. | <b>T2EE100</b><br><b>FAG</b><br>Fag, Tapered Roller Bearing, Tapered<br>Roller Bearings T. Mai |  | UNIT  |
| <b>ÝIB</b>        |  |              |  |  |  |       |
|                   |  |              |  |  |  | SHEET |